



FULL HD
1920x1080

LCD 32_42_46_52
PD 50



In questa gamma il materiale diventa l'interprete di un'estetica sempre più sorprendente, dove l'unicità del prodotto si allinea alle tendenze di uno stile tutto italiano. Leggeri profili in Alluminio cromato brillantato per il Frame, arricchiti da cristallo temperato Black.

Inoltre, una nuovissima combinazione stilistica: un materiale unico ed esclusivo come lo specchio per la proposta Mirror, disponibile nei sizes 32" e 42".

In questa gamma Hantarex arricchisce l'offerta dei televisori a grande formato, LCD 42", 46", 52" e PD 50"; quattro modelli con pannello LCD/PD ad altissima risoluzione Full HD 1080p da 1920x1080 pixels. Un design essenziale per un formato Home Cinema.

In this range, the material expresses the evermore surprising style where the uniqueness of the product aligns with the taste of one style completely Italian.

Light shiny, chromed aluminum profiles for the frame, enriched by beautiful tempered glass in Black.

Moreover, the new style combination of unique and exclusive material such as the mirror for the Mirror model, available in 32" a 42" models. In this range, Hantarex enriches the range of large format televisions, LCD 42", 46", 52" and PD 50" models; four models of LCD/PD panels with Full HD 1080p with 1920x1080-pixel resolution. An essential design for Home Cinema format.

HDMI
HIGH DEFINITION MULTIMEDIA INTERFACE



STRIPES LINE



Principali Caratteristiche:

- LCD 32" con funzionalità HD Ready
- LCD da 52", 46", 42", con funzionalità Full HD 1080p
- PD 50" con funzionalità Full HD 1080p
- Connessioni HDMI
- Doppio Tuner Analogico + Digitale
- Integrazione del decoder Digitale Terrestre DVB-T Free to Air
- Finiture cromatiche Black e Mirror
- Struttura in alluminio con profili cromati brillantati
- Common Interface Slot SmarCam

Principal Characteristics:

- LCD 32" with HD Ready functionality
- LCD 52", 46", 42" with Full HD 1080p functionality
- PD 50" with Full HD 1080p functionality
- HDMI connections
- Double Analog + Digital Tuner
- Integrated Digital Terrestrial DVB-T Free to Air
- Various colors: Black and Mirror
- Aluminium frame with shiny chromed profiles
- Common Interface Slot SmarCam

DVB T
TERRESTRIAL

Ricerca stilistica ed innovazione tecnologica.

Una mission aziendale che Hantarex rinnova continuamente e che diventa tratto distintivo anche per la nuova gamma Stripes Glass Line, della Home TV Collection 2009. Una collezione dal design essenziale, che trasmette una sensazione immediata di eleganza, attraverso la purezza delle sue linee, in diverse combinazioni cromatiche e in diversi formati: LCD 32", 42", 46", 52" e PD 50" di pura tecnologia, tecnologia Hantarex.

Stylistic research and innovated technology.

Hantarex's mission is to renew its products continuously. This is the distinctive trait of the new Stripes Line of the 2009 Home TV Collection. This is a collection with essential design that transmits a sensation of elegance and preciousness through the pure lines available in various colors and formats: LCD 32", 42", 46", 52" and PD 50" of pure technology for Hantarex's LCD TVs.



TECHNICAL DATA



Product name:

STRIPES LCD 32 HD DVB-T CI *

STRIPES LCD 42 FULL HD DVB-T CI *

STRIPES LCD 46 FULL HD DVB-T CI

STRIPES LCD 52 FULL HD DVB-T CI

DISPLAY PANEL	CONNECTIONS	FEATURES	CONTROLS	PHYSICAL	ACCESSORIES
<p>Screen size: 32" (81 cm) diagonal Aspect Ratio: 16:9 Resolution: 1366 (H) x 768 (V) pixels Brightness: 400 cd/m² Contrast ratio: 1500:1 Response time: 8 msec View angle: H: 178°; V: 178° Colors: 16.7 Ml</p>	<p>Video: 1 x RCA Video [CVBS] 1 X Mini Din 4 pin S-Video [YC] SCART1 [Full], SCART2 [CVBS, YC] 3 X RCA Component [Y, Pb, Pr] 1 X Dsub 15 pin HD Analog RGB [PC] HDMI 1, HDMI 2 Antenna [FS Chm - VHF/UHF/DVB-T] 2 X RCA Video / S-Video stereo input 2 X RCAComponent stereo input 1 X Jack 3.5 mm PC stereo input 1 X Jack 3.5 mm Cuffia</p> <p>Control: Local Key board Remote control 1 X Dsub 9 pin RS232 Common Interface Memory Card Reader USB 2.0, SD</p>	<p>Video: PAL (BGHDMI, M, N, 60), SECAM CVBS: 1 Vpp / 75 Ohm - nominal (with AGC) Y/C: 1 Vpp / 75 Ohm - nominal (with AGC) Y/Pb/Pr: 0.7 Vpp / 75 Ohm VGA - SXGA (1366x768) 480i/p, 576i/p, 720p, 1080i/p Standard: PAL, BGR/DK, SECAM, LL' Tuning system: Electronic with PLL Teletext: BISS/15/TOPTFAST DVB-T Digital Tuner MPEG-2 MP@ML video MPEG-1 audio layer I/II Common Interface Memory Card Reader/SD / MMC / MS / CF USB 2.0</p> <p>Audio: Power audio output: 2 x 9W Built-in stereo speakers / External speakers HD Ready</p>	<p>Video: Brightness, Contrast, Color, Sharpness, Tint Colour temperature (3 selections, user) Size (16:9, 14:9, 4:3, Zoom, Original, Full screen) PIP (when in graphic mode) SBS Auto scan / Auto sort Manual scan / fine tune Auto station name LNA (Low Noise Amplifier) Edit program Volume, Balance SRS Stereo/monobaur sound/NICAM 3D Comb Filter Stand-by mode Timer (sleep) Backlight control Programmable OSD NL, ES, FR, GB, IT, N</p>	<p>Dimensions: 815(W) X 518 (H) X 104 (D) (without base) 815(W) X 605 (H) X 103 (D) (with base) 21 Kg (without base) 115/230 VAC ± 15%, 50/60 Hz 150 W</p>	<p>Pedestal / Wall mount (opt) Power cable Remote control with batteries User manual</p>
<p>Screen size: 42" (107 cm) diagonal Aspect Ratio: 16:9 Resolution: 1920 (H) x 1080 (V) pixels Brightness: 500 cd/m² Contrast ratio: 4,000:1 Response time: 8 msec View angle: H: 178°; V: 178° Colors: 16.7 Ml</p>	<p>Video: 1 x RCA Video [CVBS] 1 X Mini Din 4 pin S-Video [YC] SCART1 [Full], SCART2 [CVBS, YC] 3 X RCA Component [Y, Pb, Pr] 1 X Dsub 15 pin HD Analog RGB [PC] HDMI 1, HDMI 2 Antenna [FS Chm - VHF/UHF/DVB-T] 2 X RCA Video / S-Video stereo input 2 X RCAComponent stereo input 1 X Jack 3.5 mm PC stereo input 1 X Jack 3.5 mm Cuffia</p> <p>Control: Local Key board Remote control 1 X Dsub 9 pin RS232 Common Interface Memory Card Reader USB 2.0, SD</p>	<p>Video: PAL (BGHDMI, M, N, 60), SECAM CVBS: 1 Vpp / 75 Ohm - nominal (with AGC) Y/C: 1 Vpp / 75 Ohm - nominal (with AGC) Y/Pb/Pr: 0.7 Vpp / 75 Ohm VGA - SXGA (1366x768) 480i/p, 576i/p, 720p, 1080i/p Standard: PAL, BGR/DK, SECAM, LL' Tuning system: Electronic with PLL Teletext: BISS/15/TOPTFAST DVB-T Digital Tuner MPEG-2 MP@ML video MPEG-1 audio layer I/II Common Interface Memory Card Reader/SD / MMC / MS / CF USB 2.0</p> <p>Audio: Power audio output: 2 x 9W Built-in stereo speakers / External speakers HD Ready</p>	<p>Video: Brightness, Contrast, Color, Sharpness, Tint Colour temperature (3 selections, user) Size (16:9, 14:9, 4:3, Zoom, Original, Full screen) PIP (when in graphic mode) SBS Auto scan / Auto sort Manual scan / fine tune Auto station name LNA (Low Noise Amplifier) Edit program Volume, Balance SRS Stereo/monobaur sound/NICAM 3D Comb Filter Stand-by mode Timer (sleep) Backlight control Programmable OSD NL, ES, FR, GB, IT, N</p>	<p>Dimensions: 1034(W) X 647 (H) X 102 (D) (without base) 1034(W) X 735 (H) X 102 (D) (with base) 33 Kg (without base) 115/230 VAC ± 15%, 50/60 Hz 230 W</p>	<p>Pedestal / Wall mount (opt) Power cable Remote control with batteries User manual</p>
<p>Screen size: 46" (117 cm) diagonal Aspect Ratio: 16:9 Resolution: 1920 (H) x 1080 (V) pixels Brightness: 500 cd/m² Contrast ratio: 3,000:1 Response time: 8 msec View angle: H: 178°; V: 178° Colors: 16.7 Ml</p>	<p>Video: 1 x RCA Video [CVBS] 1 X Mini Din 4 pin S-Video [YC] SCART1 [Full], SCART2 [CVBS, YC] 3 X RCA Component [Y, Pb, Pr] 1 X Dsub 15 pin HD Analog RGB [PC] HDMI 1, HDMI 2 Antenna [FS Chm - VHF/UHF/DVB-T] 2 X RCA Video / S-Video stereo input 2 X RCAComponent stereo input 1 X Jack 3.5 mm PC stereo input 1 X Jack 3.5 mm Cuffia</p> <p>Control: Local Key board Remote control 1 X Dsub 9 pin RS232 Common Interface Memory Card Reader USB 2.0, SD</p>	<p>Video: PAL (BGHDMI, M, N, 60), SECAM CVBS: 1 Vpp / 75 Ohm - nominal (with AGC) Y/C: 1 Vpp / 75 Ohm - nominal (with AGC) Y/Pb/Pr: 0.7 Vpp / 75 Ohm VGA - SXGA (1366x768) 480i/p, 576i/p, 720p, 1080i/p Standard: PAL, BGR/DK, SECAM, LL' Tuning system: Electronic with PLL Teletext: BISS/15/TOPTFAST DVB-T Digital Tuner MPEG-2 MP@ML video MPEG-1 audio layer I/II Common Interface Memory Card Reader/SD / MMC / MS / CF USB 2.0</p> <p>Audio: Power audio output: 2 x 9W Built-in stereo speakers / External speakers HD Ready</p>	<p>Video: Brightness, Contrast, Color, Sharpness, Tint Colour temperature (3 selections, user) Size (16:9, 14:9, 4:3, Zoom, Original, Full screen) PIP (when in graphic mode) SBS Auto scan / Auto sort Manual scan / fine tune Auto station name LNA (Low Noise Amplifier) Edit program Volume, Balance SRS Stereo/monobaur sound/NICAM 3D Comb Filter Stand-by mode Timer (sleep) Backlight control Programmable OSD NL, ES, FR, GB, IT, N</p>	<p>Dimensions: 1150(W) X 710 (H) X 105 (D) (without base) 1150(W) X 797.5 (H) X 105 (D) (without base) 40Kg (without base) 115/230 VAC ± 15%, 50/60 Hz 230 W</p>	<p>Pedestal / Wall mount (opt) Power cable Remote control with batteries User manual</p>
<p>Screen size: 52" (132 cm) diagonal Aspect Ratio: 16:9 Resolution: 1920 (H) x 1080 (V) pixels Brightness: 500 cd/m² Contrast ratio: 3,000:1 Response time: 8 msec View angle: H: 178°; V: 178° Colors: 16.7 Ml</p>	<p>Video: 1 x RCA Video [CVBS] 1 X Mini Din 4 pin S-Video [YC] SCART1 [Full], SCART2 [CVBS, YC] 3 X RCA Component [Y, Pb, Pr] 1 X Dsub 15 pin HD Analog RGB [PC] HDMI 1, HDMI 2 Antenna [FS Chm - VHF/UHF/DVB-T] 2 X RCA Video / S-Video stereo input 2 X RCAComponent stereo input 1 X Jack 3.5 mm PC stereo input 1 X Jack 3.5 mm Cuffia</p> <p>Control: Local Key board Remote control 1 X Dsub 9 pin RS232 Common Interface Memory Card Reader USB 2.0, SD</p>	<p>Video: PAL (BGHDMI, M, N, 60), SECAM CVBS: 1 Vpp / 75 Ohm - nominal (with AGC) Y/C: 1 Vpp / 75 Ohm - nominal (with AGC) Y/Pb/Pr: 0.7 Vpp / 75 Ohm VGA - SXGA (1366x768) 480i/p, 576i/p, 720p, 1080i/p Standard: PAL, BGR/DK, SECAM, LL' Tuning system: Electronic with PLL Teletext: BISS/15/TOPTFAST DVB-T Digital Tuner MPEG-2 MP@ML video MPEG-1 audio layer I/II Common Interface Memory Card Reader/SD / MMC / MS / CF USB 2.0</p> <p>Audio: Power audio output: 2 x 9W Built-in stereo speakers / External speakers HD Ready</p>	<p>Video: Brightness, Contrast, Color, Sharpness, Tint Colour temperature (3 selections, user) Size (16:9, 14:9, 4:3, Zoom, Original, Full screen) PIP (when in graphic mode) SBS Auto scan / Auto sort Manual scan / fine tune Auto station name LNA (Low Noise Amplifier) Edit program Volume, Balance SRS Stereo/monobaur sound/NICAM 3D Comb Filter Stand-by mode Timer (sleep) Backlight control Programmable OSD NL, ES, FR, GB, IT, N</p>	<p>Dimensions: 1306(W) X 817 (H) X 111 (D) (without base) 1306(W) X 899 (H) X 111 (D) (without base) 48 Kg (without base) 115/230 VAC ± 15%, 50/60 Hz 350 W</p>	<p>Pedestal / Wall mount (opt) Power cable Remote control with batteries User manual</p>

Digital Video Broadcasting Common Interface (or DVB-CI), is a DTT feature integrated in the new 2009 HANTAREX Stripes TV range. The CI enables the addition and use of a 'conditional access module', also known as CAM, which adapts the TV set functionalities to different kinds of cryptography decoding.

From DVB standards, a TV set with an integrated CI slot means a TV set with an integrated PCMCIA connector accepting CAM device, in which the user can insert the Pay-per View cards issued by the broadcasters with payable contents.

Indeed, one of DVB main strengths, by means of CI and CAM device, is the option of implementing the required conditional access capability on the common interface.

This allows broadcasters to use modules containing solutions from different suppliers in the same broadcast system, thus increasing their choice and anti-piracy options.



* DISPONIBILE ANCHE NELLESLUSIVA
VERSIONE MIRROR
ALSO AVAILABLE IN MIRROR
EXCLUSIVE VERSION





Product name: STRIPES PD 50" FULL HD DVB-T TV

	DISPLAY PANEL
	<p>Screen size: 50" (127cm) diagonal Aspect Ratio: 16:9 Resolution: 1920 (H) x 1080 (V) pixels Brightness: 1,200 cd/m² Contrast ratio: 30,000:1 (typical) View angle: H: 178° - V: 178° Colors: 16.7 Mill</p>
CONNECTIONS	<p>Video: Video (CVBS) S-Video (Y/C) SCART1 (CVBS, RGB), SCART2 (CVBS) Component (Y, Pb, Pr) Analog RGB (PC) PC: HDMI 1, HDMI 2, HDMI 3 (HDCP) Tuner: Antenna (75 Ohm - VHF/UHF/DVB-T) Audio: Video / S-Video stereo input Component stereo input PC stereo input Line stereo output Optical audio output (SPDIF) Power stereo output (speakers clinch) RS232</p>
FEATURES	<p>Control: PAL (BGH/DI, M, N, 60), NTSC (M, 4-43), SECAM Video: VGA - SXGA (1280x1024) PC: NATIVE (1368x768) 480i/p, 576i/p, 720p, 1080i @ 50/60 Hz DTV: Standard: PAL BG/DK, SECAM L/L Tuner: Tuning system: Electronic with PLL Teletext: BESC1, ST/OP/FAST DVB-T: DVB-T Digital Tuner MPEG-2 MP@ML video MPEG-1 audio layer I&II, AC-3 through SPDIF Channel Banner, Parental Control, EPG Power audio output: 2 x 7W Audio: Built-in stereo speakers / External speakers Speakers: HD Ready Others: Sky HD tested</p>
CONTROLS	<p>Video: Brightness, Contrast, Color, Sharpness Colour temperature (5 selections, user) Size (16:9, 14:9, 4:3, Panorama, Zoom, Auto) PIP / POP / Split Screen Still Auto scan / Auto sort Manual scan / fine tune Auto station name LNA (Low Noise Amplifier) Edit program Volume, Balance Equalizer (8 band) TV: Internal/External speaker selection Stereo/monospatial sound/NCAM AutomaticVolumeControl 3D Comb Filter Share by mode Timer (wake-up, sleep) Others: Screensaver (orbital, wipe, blue, gray) Programmable OSD DE, ES, FR, GB, IT, NL, PT, RU</p>
PHYSICAL	<p>OSD Language: 1216 (W) x 744 (H) x 110 (D) (without base) Dimensions: 55 Kg (without base) Weight: 115/230 (VAC ± 15%, 50/60 Hz) Main voltage: 430 W</p>
ACCESSORIES	<p>Power consumption: Power cable Remote control with batteries User manual</p>



STRIPES LINE HOME TV COLLECTION 2009 05/09

Le specifiche di prodotto possono cambiare anche senza preavviso. SAMBERS ITALIA S.p.A. si riserva il diritto di modificare parzialmente o integralmente le informazioni riportate in questo documento. Product specifications are subject to change without any notification. SAMBERS reserve the right to modify part or whole contents of the specification contained in this document.

www.hantarex.eu



HANTAREX È PRODOTTO E DISTRIBUITO DA: ein Produkt von Audio Tuning Vertriebs GesmbH - Vienna www.audiotuning.com

SAMBERS

I T A L I A

Headquarter:

via Friuli 10/D
20046

Biassono (Mi)

tel. +39.039.2224.1

fax +39.039.2224.200

www.hantarex.it

info@hantarex.it



UNI EN ISO 9001:2000